



LINKSMART®

WITH *San-a-Key*

Disinfectable Backlit Keyboard with Biometrics & RFID

KSI-1802R SX HFFFB-21

Integrated Multifactor Authentication with a Complete User-Defined Infection Control Program



Integrated fingerprint biometrics | Contactless RFID logon-logoff
EPCS compliant | Electronic health records protection
Password replacement solution | Backlit keys with three levels of illumination
Crevice-free surface prevents penetration of dirt and germs
Cleaning button disables keys for disinfection
Increased workflow

- Mix and match security features
- Multifactor authentication is part of your zero trust strategy
- Award-winning Linksmart® cleaning button and San-A-Key® software aid desktop infection control
- Compatible with leading healthcare SSO security applications



Infection Control and Desktop Security



rfIDEAS card readers secure the desktop with quick contactless smart card logon



KSI's LinkSmart® powered by San-a-Key® is a complete infection control solution for the clinical desktop



Pro-grade, silicon-surfaced fingerprint sensor offers strong authentication

Made for healthcare

The mix-and-match KSI-1802 SX keyboard is a premier input device that secures the desktop and helps clinicians fight germs



Compatible with leading SSO software and healthcare platforms

FEATURES

- 500 dpi fingerprint biometrics
- Dual band, contactless RFID badge reader
- Multifactor authentication
- ePrescribe and I-STOP ready
- GSA FIPS 201 compliant
- LinkSmart® push-to-clean keyboard locking system
- Durable, chemical-resistant, scrubbable surface
- Easy disinfection with standard, approved wipes
- San-a-Key® monitoring of infection control compliance
- Detachable USB for quick removal from service
- Three levels of backlit illumination
- Compact footprint fits standard medical carts
- Windows 8, 10, 11 and Linux compatible

SPECIFICATIONS

- Weight: 2.2 lbs.
- Dimensions: 7-3/8" D x 15" W x 1-5/16" H
- Black, White, Red, and custom colors
- High-speed USB interface
- HID® TCS1 silicon-surfaced 500 dpi sensor
- rfIDEAS OEM-805N21KU-X card reader
125 kHz & 13.56 Mhz
- LEDs flash during cleaning mode
- International layouts available



(510) 562-5000
 (510) 562-0689 fax
 14494 Wicks Boulevard
 San Leandro, CA 94577
 sales@ksikeyboards.com

ksikeyboards.com sanakey.com
 Follow us online @ksikeyboards



Patent # US8, 119 B1